

**Amendments to the Claims:**

1. (Previously Presented) A method for use with a wireless mobile station that is adapted and configured to interact with a wireless communication system using at least a first, second, and third mode of operation, wherein the first mode of operation comprises an active mode of operation where the mobile station actively uses an allocated communications channel, the third mode of operation comprises a dormant mode of operation where the mobile station is without an allocated communications channel, and the second mode of operation comprises a semi-dormant mode of operation where the mobile station maintains at least a portion of the allocated channel, comprising:

- monitoring at least one indicator of relative mobility regarding the rate of movement of the wireless mobile station within the wireless communication system to provide a mobility indicia;
- using the mobility indicia to adjust a first inactivity temporal window during at least one of the modes of operation wherein the first inactivity temporal window determines a duration the wireless mobile station remains in the at least one of the modes of operation, and
- using the mobility indicia to adjust a second inactivity temporal window during at least another of the one of the modes of operation wherein the second inactivity temporal window determines a duration the wireless mobile station remains in the at least another of the one of the modes of operation and wherein a duration of the first inactivity temporal window is extended and a duration of the second inactivity temporal window is decreased depending on the mobility indicia.

2. (Original) The method of claim 1 wherein monitoring at least one indicator of relative mobility regarding the wireless mobile station further comprises monitoring a hand-off rate as corresponds to the wireless mobile station.

3. (Original) The method of claim 1 wherein monitoring at least one indicator of relative mobility regarding the wireless mobile station further comprises accessing at least one metric that corresponds to radio frequency measurement report messages.

4. (Original) The method of claim 3 wherein accessing at least one metric that corresponds to radio frequency measurement report messages further comprises accessing a metric that corresponds to a rate at which the wireless mobile station transmits radio frequency measurement report messages.

5. (Previously Presented) The method of claim 1 and further comprising:

- determining an operating capability of the wireless mobile station;
- modifying at least one of the first and second inactivity temporal window as a function, at least in part, of the operating capability of the wireless mobile station.

6. (Original) The method of claim 2 wherein monitoring a hand-off rate as corresponds to the wireless mobile station further comprises monitoring a hand-off rate for at least a predetermined amount of time as corresponds to the wireless mobile station.

7. (Original) The method of claim 1 wherein monitoring at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia further comprises monitoring at an infrastructure element of the wireless communication system at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia.

8. (Original) The method of claim 1 wherein monitoring at an infrastructure element of the wireless communication system at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia further comprises monitoring at a radio access network (RAN) at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia.

9. (Original) The method of claim 1 wherein monitoring at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia further comprises monitoring at the wireless mobile station at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia.

10-11. (Cancelled)

12. (Previously Presented) The method of claim 1 wherein using the mobility indicia to adjust at least one of the first and second inactivity temporal window during a mode of operation further comprises using the mobility indicia to adjust a first inactivity temporal window during the first mode of operation to thereby dynamically control a duration of inactivity prior to automatically causing the wireless mobile station to cease using the first mode of operation and to begin using the second mode of operation.

13. (Previously Presented) The method of claim 1 wherein using the mobility indicia to adjust one of at least a first and a second inactivity temporal window during a mode of operation further comprises, when the mobility indicia corresponds to at least some predetermined amount of increased mobility, using the mobility indicia to increase an inactivity temporal window for use during the first mode of operation.

14. (Previously Presented) The method of claim 1 wherein using the mobility indicia to adjust one of at least a first and a second inactivity temporal window during a mode of operation further comprises using the mobility indicia to adjust an inactivity temporal window during the second mode of operation to thereby dynamically control a duration of inactivity prior to automatically causing the wireless mobile station to cease using the second mode of operation and to begin using a different mode of operation.

15. (Previously Presented) The method of claim 1 and further comprising:

- monitoring wireless communication system setup times to provide a setup time indicia;
- using the setup time indicia to further adjust at least one of the first and second inactivity temporal window during the mode of operation.

16. (Original) The method of claim 15 wherein monitoring wireless communication system setup times to provide a setup time indicia further comprises monitoring wireless

communication system setup times for a plurality of wireless communication units to provide a setup time indicia.

17. (Previously Presented) The method of claim 15 wherein using the setup time indicia to further adjust at least one of the first and second inactivity temporal window during the mode of operation further comprises increasing the first inactivity temporal window in response to a setup time indicia that reflects a setup time delay that has increased by at least more than a predetermined amount.

18. (Previously Presented) The method of claim 15 wherein using the setup time indicia to further adjust at least one of the first and second inactivity temporal window during the mode of operation further comprises decreasing the second inactivity temporal window in response to a setup time indicia that reflects a setup time delay that has decreased by at least more than a predetermined amount.

19. (Previously Presented) The method of claim 1 wherein using the mobility indicia to adjust at least one of a first and a second inactivity temporal window during a mode of operation further comprises using the mobility indicia to adjust an inactivity temporal window for use during at least two different modes of operation.

20-26. (Cancelled)

27. (Previously Presented) A method for use with a wireless mobile station that is adapted and configured to interact with a wireless communication system using at least a first, second, and third mode of operation, wherein the first mode of operation comprises an active mode of operation where the mobile station actively uses an allocated communications channel, the third mode of operation comprises a dormant mode of operation where the mobile station is without allocated communications channel, and the second mode of operation comprises a semi-dormant mode of operation where the mobile station maintains at least a portion of the allocated channel, comprising:

- monitoring at least one indicator of communication resources setup delay information as corresponds to the wireless communication system to provide a setup delay indicia;
- using the setup delay indicia to adjust a first inactivity temporal window as corresponds to the wireless mobile station during a mode of operation wherein the inactivity temporal window determines a duration the wireless mobile station remains in one of the first, second and third mode of operation, and
- using the setup delay indicia to adjust second inactivity temporal window as corresponds to the wireless mobile station during another mode of operation wherein the second inactivity temporal window determines a duration the wireless mobile station remains in another of the first, second and third mode of operation and wherein a duration first inactivity temporal window is extended and a duration of the second inactivity temporal window is decreased depending on the setup delay indicia.

28. (Original) The method of claim 27 wherein monitoring at least one indicator of communication resources setup delay information as corresponds to the wireless communication system further comprises monitoring at least one indicator of communication resources setup delay information as corresponds to the wireless communication system for a plurality of wireless mobile stations.

29. (Previously Presented) The method of claim 27 and further comprising:

- monitoring at least one indicator of relative mobility regarding the wireless mobile station to provide a mobility indicia;
- using the mobility indicia to further adjust the first and the second inactivity temporal window during the mode of operation.